



FKG1XP

Generator Circuit Breaker System for Power Plants from 600 to 750 MW*

Power plant owners are concerned with the availability and reliability of their plants. That is why it is crucial to rely on equipment capable of safely interrupting fault conditions while protecting connected equipment and reduce outage periods.

Higher Reliability

FKG Generator circuit breakers are equipped with a fully spring-operated mechanism for high reliability, maximum energy stability and low maintenance requirements. This model is equipped with additional fans and a smart cooling system to optimize thermal exchanges.

Keep an Eye on your Generator Circuit-Breaker

The FKG1XP includes a smart cooling digital solution to optimize in real time the ventilation system and retrieve main GCB information through industrial network communication or local Human Machine Interface.

In addition: The FKG1XP figures out optional add-on CBWatch monitoring system (automatic diagnosis) for maintenance based on real status of the switchgear.


Higher Safety

A true electro-mechanical sequential interlocking system assures a reliable mechanical and electrical coordination for higher safety.

Components and Single Line Diagram

- 1 - Circuit breaker
- 2 - Disconnecter
- 3 - Earthing switch
- 4 - Starting switch
- 5 - Capacitors

- 6 - ZnO Surge arresters
- 7 - Current transformers
- 8 - Voltage transformers
- 9 - Manual Short-Circuiting Bar



Technical Data

- 21,000 A - 160 kA - 50 Hz
- 20,450 A - 160 kA - 60 Hz

Key Benefits

- Utmost reliability of the full spring mechanism
- CBWatch makes proactive maintenance possible
- Interrupting chambers with natural cooling system
- Ideal for large & very large turbines or generators

Testing and Quality

- Product in full compliance with IEC/IEEE 62271-37-013 GCB standard
- Manufacturing ISO 9001 and ISO 14001 certified
- S.E.I. - S.N.E. and national packing procedures

* Depending upon the power station's specifications, GE may propose an alternative GCB power rating.





Technical Specifications

FKG1XP

Rated maximum voltage	kV	32.4			
Short-circuit breaking current	kA	up to 160			
Rated out-of-phase breaking current	kA	80			
Rated breaking time	ms	75			
Rated closing time	ms	100			
Insulating gas		SF ₆			
Rated absolute pressure at 20°C	kPa	950			
Minimum absolute pressure at 20°C	kPa	800			
Location		Indoor / Outdoor (protected)			
Breaker cooling type		Natural			
Ambient air temperature limits	°C	-20°C(-25°C)/+40°C			
Busbar temperature limit/Enclosure temperature limit	°C	90/70°C		105/80°C	
Frequency	Hz	50	60	50	60
Maximum rated normal current					
- Indoor with ambient air 40°C	A	21,000	20,450	20,000	19,450
- Outdoor with ambient air 40°C	A	20,300	19,700	19,300	18,700
Phase spacing A with 100 mm step	mm	1,600 to 2,000			
Protection degrees (enclosure / cubicles)		IP65 / IP55			
SF ₆ monitoring by densimeter		3-phase			
Pressure reading		Yes			

		FKG1X Circuit Breaker	SKG1X Disconnecter	MKG1X Earthing switch	IKG1 Starting switch
Rated peak withstand current	kA _{peak}	440	440	440	330
Rated short time withstand current	kA	160	160	160	100
Rated duration of short-circuit	s	3	3	2	1
Rated insulation level (at sea level) - Phase to earth					
- Rated power frequency withstand voltage	kV	80	80		30
- Rated lightning impulse withstand voltage: wave 1,2/50 μs	kV _{peak}	150	150		60
Rated insulation level (at sea level) - Across terminals					
- Rated power frequency withstand voltage	kV	80	90	80	80
- Rated lightning impulse withstand voltage: wave 1,2/50 μs	kV _{peak}	150	165	150	150

Dimensions



For more information please contact
GE
Grid Solutions

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact
Phone: +44 (0) 1785 250 070

GEGridSolutions.com

IEC is a registered trademark of Commission Electrotechnique Internationale.
IEEE is a registered trademark of the Institute of Electrical Electronics Engineers, Inc.

GE and the GE monogram are trademarks of General Electric Company.

GE reserves the right to make changes to specifications of products described at any time without notice and without obligation to notify any person of such changes.

FKG1XP-Brochure-EN-2021-08-Grid-AIS-0136. © Copyright 2021, General Electric Company.
All rights reserved.

