

Kelman MINITRANS™

Cost-effective on-line DGA & moisture for transformers

Product Overview

Knowledge of the condition of transformers is essential for all electrical networks and on-line monitoring of transformers is an increasingly vital component of successful asset management programs. The information provided by multi-gas on-line DGA allows valuable asset capabilities to be maximized and expensive failures to be avoided.

Dissolved Gas Analysis (DGA) and moisture measurement of the insulation oil are recognized as the most important tests for condition assessment of any tank of a transformer. Traditionally performed in a laboratory environment, the MINITRANS provides for partial on-line discrete DGA and moisture monitoring.

Key Benefits

- Cost effective on-line DGA
- Remote insight into transformer condition
- Discrete measurement of key gases associated with arching cellulose degradation and general fault conditions
- Faults can be detected in infancy
- Generic fault type can be classified from results
- Transformer load and output can be optimized safely
- Aids condition based and predictive maintenance strategies
- Available with AC or AC/DC power supply

Applications

Multi-Gas DGA has traditionally been confined to infrequent off-line laboratory analysis, forming part of time based maintenance strategies. Globally the average age of transformers continues to increase, whilst in comparison to historical experience a larger percentage of new transformers encounter faults in their early years of operation. This means the possibilities of rapid aging, unplanned outages and even catastrophic failures between off-line tests also increases leading many asset owners to adopt on-line DGA monitoring equipment more suited to condition based/predictive maintenance strategies.

The MINITRANS facilitates entry into discrete on-line DGA and moisture monitoring for transformers and other oil insulated filled electrical equipment. Discretely measuring 3 key gases: Hydrogen; Carbon Monoxide and Acetylene; plus Moisture, MINITRANS gives insight on developing faults, paper degradation and electrical arching providing trending of gas-in-oil through its close integration with GE's powerful Perception software suite and/or users own software, historian and SCADA systems. At a price that facilitates higher volumes of monitor deployment, MINITRANS can be utilized to monitor any size of transformer but is most widely employed to expand multi-gas on-line DGA coverage beyond the typical candidates of large, system critical or compromised transformers helping asset owners incorporate on-line DGA across a larger portion of their fleet, with a view to extending asset life, preventing unexpected failure and operating on a condition based/predictive maintenance schedule.

- Auxiliary GSU transformers
- On load tap changers
- Transmission transformers
- Distribution transformers



Integrated Solution

- Key element of GE's integrated transformer monitoring system
- Operates as standalone DGA monitor or can be integrated with bushing monitoring and transformer modelling modules
- Integrated load monitoring allows DGA results to be analyzed against the loading of the transformer
- Can be controlled and configured by GE's Perception™ software – single platform advanced asset management suite providing sophisticated graphical trending & diagnostic analysis of results

Cutting Edge Technology

- Three key fault gases plus moisture
- Automated headspace gas extraction
- State of the art photo-acoustic spectroscopy (PAS) measurement technology
- No carrier or calibration gases required
- Long service life with minimal maintenance
- Capable of sampling frequency up to once per hour

Ease of Use

- Easy installation: no outages required reducing expense and inconvenience for user
- No consumables and minimal maintenance requirements reduces running costs and site visits
- Extensive local and remote communications options available
- Sampling frequency user-configurable, versatile and flexible
- LCD display provides up to date information on site

Configurable Alerts

- Two sunlight visible front panel LED arrays (Red & Yellow)
- User configurable relay contact
- Alarms can be set or changed locally or remotely using Perception software
- Caution and alarm modes can be used to automatically increase sampling frequency

Communication

- Two separate channels for remote communications, local USB connection and Ethernet connection
- Communications protocols supported include MODBUS®, MODBUS/TCP, DNP3.0, IEC®61850
- Modules available for communication via RS232, RS485, Ethernet, Fiber Optic, PSTN and cellular GSM/GPRS modems

Technical Features

- Uses photo-acoustic spectroscopy (PAS) to give highly reliable results. Field proven with over 8,000 Kelman PAS systems deployed in over ninety countries worldwide
- Three target gases plus moisture measured
- Fully embedded processor and internal data storage for – 10,000 records - over eight years of data at default sampling rates
- Non-volatile memory storage to prevent loss of data
- Discrete sampling gives more rapid response to gas rises. No 'averaging' of DGA results

Technical Specifications

| PARAMETER (COMPOUND) | VALUE/MEETS (MEASUREMENT RANGE) |
|--|--|
| Hydrogen (H ₂) | 5 - 5,000 ppm |
| Carbon Monoxide (CO) | 10 - 50,000 ppm |
| Acetylene (C ₂ H ₂) | 3 - 50,000 ppm |
| Moisture (H ₂ O) | 0 - 100% RS (given in ppm) |
| Accuracy* | ±10% or ±LDL (whichever is greater) |

*Accuracy quoted is the accuracy of the detectors during calibration.


| ENVIRONMENT | |
|----------------------------------|--|
| Operating Ambient Temperature | -35°C to +55°C (-40°F to +131°F): AC version -17°C to +55°C (1°F to +131°F): AC/DC version |
| Oil Temperature at valve** | -10°C to +100°C (14°F to +212°F) |
| Power Requirements AC version*** | Nom: 115/230 Vac, Range: 103-126/207-253 Vac, 47-63 Hz, 6A max |
| Power Requirements AC/DC version | Nom: 100-230 Vac, Range: 90-253 Vac, 45-65Hz, 5A max Nom: 100-220 Vdc, Range: 90-242 Vdc, 45-65Hz, 5A max |
| Operating Ambient Humidity | 0-95% RH, non-condensing |
| Enclosure | IP55 certified, 304 Stainless Steel (316L option) |
| Mechanical | 600mm (24") x 380mm (15") x 350mm (14"), Installed weight 31Kg (68lb), shipping weight 49Kg (108lb) |
| Single Phase Alarm Relays | NO and NC provided: 1A@250Vac, 200mA@125Vdc, 150mA@300Vdc, 1A@30Vdc |
| Sampling Frequency | Variable - once per hour to once every 4 weeks |

**Based on testing carried out using VOLTESSO™ 35 mineral oil, over a ¼" pipe run of 10 metres or less from oil supply or return valve to monitor connection point and on transformer oil supply valve volumes of 200ml or less. For oil temperatures colder than -10°C GE recommend the use of heat trace cabling on piping

***AC input auto-switching

Perception - Transformer Fleet Management & Risk Software


Providing critical insight on your transformers condition and overall fleet risk. Perception features data trending, condition diagnostics, customizable overview reports, wallboard fleet visualization, alarm notification and visualization. The smart and standards based logic used in Perceptions fleet ranking algorithms deliver a simplified yet concise overview of your transformers condition and risk. The customizable data import and export facility enhances Perceptions interoperability and the expert email notifications ensures the right person receives critical data should a transformers condition change.



Fleet health/risk overview




Transformer health/risk overview



Customizable reporting



Wallboard visualization



Advanced Diagnostics

*Note - exact feature will depend on Perception version purchased



Digital Energy
Lissie Industrial Estate East Lissie Road
Lisburn BT28 2LU United Kingdom
Tel: +44 (0) 2892 622915
gedigitalenergy@ge.com
GEDigitalEnergy.com

Copyright 2015, General Electric Company. All Rights Reserved.
GE, the GE monogram, Kelman, MINITRANS and Perception are trademarks of the General Electric Company.
Modbus is a registered trademark of Schneider Automation, Inc.
IEC is a registered trademark of Commission Electrotechnique Internationale.
VOLTESSO is a registered trademark of Exxon Mobil Corporation.
GE reserves the right to make changes to specifications of products described at any time without notice and without obligation to notify any person of such changes.

Alarms

- Two sunlight visible front panel LED arrays (Red & Green)
- All alarms can be set or changed locally or remotely using Perception software
- Six alarm setting screens or scenarios are available, which can set alarms based on the level of the three gasses/moisture, and rates of change for each gas
- Each alarm setting screen can activate the alarm relays or send an SMS message if equipped with the optional cellular modem
- Single phase alarm relays
- Caution and alarm modes can be used to increase sampling frequency
- The alarm results of each screen are independent of the other circuits and alarm setting screens

Power Supply

- Available with AC or AC/DC power supply