Grid Solutions

MODEL 3P91

Current Transformer

Window Size 2.12"





Application

3 phase relay, metering and motor overload protection.

Frequency

50-400 Hz.

Insulation Level

600 Volts, 10 kV BIL full wave.

Terminals are brass studs No. 8-32 with one flatwasher, lockwasher and regular nut.

Flexible leads U. L. 1015, 105°C., CSA approved , No. 16 AWG , 24" long are available.

Approximate weight 7 lbs.

Data Table: Model 3P91

CATALOG NUMBER	CURRENT RATIO	V.A ± 1% CLASS	ANSI METERING CLASS AT 60 Hz					SECONDARY
			B0.1	B0.2	B0.5	B0.9	B1.8	WINDING RESISTANCE (Ω @ 75°C)
3P91-101	100:5	5	1.2	1.2	4.8	4.8	-	0.032
3P91-151	150:5	5	0.6	0.6	2.4	4.8	_	0.048
3P91-201	200:5	12.5	0.6	0.6	1.2	2.4	4.8	0.064
3P91-251	250:5	20	0.3	0.3	0.6	1.2	2.4	0.080
3P91-301	300:5	35	0.3	0.3	0.6	1.2	2.4	0.097
3P91-401	400:5	50	0.3	0.3	0.3	0.6	1.2	0.129
3P91-501	500:5	80	0.3	0.3	0.3	0.6	1.2	0.162
3P91-601	600:5	85	0.3	0.3	0.3	0.6	0.6	0.194
3P91-751	750:5	90	0.3	0.3	0.3	0.6	0.6	0.196
3P91-801	800:5	100	0.3	0.3	0.3	0.3	0.6	0.209
3P91-102	1000:5	125	0.3	0.3	0.3	0.3	0.6	0.261
3P91-122	1200:5	150	0.3	0.3	0.3	0.3	0.3	0.314


Note: Captive slots on top of transformer case can be used for attaching auxiliary device mounting plate, (not supplied).


If the application requires transformer mounted relays, etc., then transformers can be ordered with secondary leads configured in various ways (consult factory).





Model 3P91





For more information, visit **gevernova.com/grid-solutions**

Instrument Transformers LLC reserve the right to change specifications of described products at any time without notice and without obligation to notify any person of such changes.

© 2025 GE Vernova and/or its affiliates. All rights reserved. GE and the GE Monogram are trademarks of General Electric Company used under trademark license.

