

GL 314 / GL 314X

Live Tank Circuit Breakers for 245 / 300 kV

GE Vernova's live tank circuit breakers for outdoor installations feature third-generation self-blast interrupter chambers and spring-operated mechanisms (FK). The field-proven interrupter chamber operates on the basis of the energy-optimized self-blast principle. The FK3 type mechanisms equip the entire range of circuit breakers with more than 250,000 references worldwide.

High Quality Components

- Single pole or three pole operating design
- Self-blast interrupter chambers
- Spring mechanism FK3 equipped with a position indicator visible from outside
- Field-proven temperature-compensated density monitor with two-stage transducer and three-color dial
- Easy access to the SF₆ filling connection (DIL0 type)
- Sealings suitable for temperatures down to -60°C / -76°F
- Hot-dip galvanized steel parts and mechanism housing made completely of aluminum

Options for Customization

- Standard low voltage equipment provided, additional equipment is available
- Composite insulators are available
- Seismic dampers for high seismic request can be provided
- Pressure relief system for passive protection of both substation and personnel
- CSD100: Point-on-wave tripping and closing relays
- Compact and modular circuit breaker monitoring solution

Enhanced Installation and Maintenance

- Preset at factory prior shipping - no adjustments during installation or commissioning
- Pole units pre-filled with SF₆ at factory before shipping
- Disassembly of interrupter chamber without removal of entire pole column possible

Rigorous Testing

GE Vernova's live tank circuit breakers meet the requirements of national and international standards. This has been confirmed by comprehensive type tests based on the latest versions of IEC standards.



Reliable Performance

Live tank SF₆ circuit breakers use self-blast technology and benefit from latest technological developments as well as our field-proven, time-tested experience in high voltage switchgear in accordance with the IEC 62271-100 standard.

Superior Manufacturing

GE Vernova's entire development and production procedures for our live tank circuit breakers are fully compliant with the latest ISO 9001, ISO 14001 and OHSAS 18001 quality standards. This ensures the high quality of our products and services and is confirmed by regular audits.

Key Benefits


- High mechanical endurance and very low restrike probability according to IEC 62271-100 class M2 & C2
- Quick and easy installation and commissioning
- Long maintenance intervals
- Proven reliability even under the most severe conditions



Dimensions (in mm / inches)

	A	C	D	E	F
GL 314	3,000 / 118.1	4,370 / 172	6,797 / 267.6	4,490 / 176.7	2,209 / 87
GL 314X - 245 kV	3,000 / 118.1	4,370 / 172	6,797 / 267.6	4,490 / 176.7	2,209 / 87
GL 314X - 300 kV	4,000 / 157.5	4,976 / 196	7,690 / 302.7	5,110 / 201.2	2,209 / 87

* Indicative values only. Final dimensions depend on configuration.



Ratings

BREAKER TYPE		GL 314		GL 314X	
Number of interrupters/phase		1		1	
Rated normal voltage	kV	245 / 252		245	300
Rated normal current	A	4,400		4,000	
Rated frequency	Hz	50	60	50	50
Rated dielectric withstand (up to 1,000 m)* (to earth / across open device)					
- At power frequency	kV	460 / 530		460 / 530	460 / 530
- At lightning impulse (1.2 / 50 µs wave)	kV (peak)	1,050 / 1,200		1,050 / 1,200	1,050 / 1,050 (+170)
- At switching impulse	kV (peak)	N/A		N/A	850 / 700 (+245)
Rated short-circuit breaking capacity -Periodic component (r.m.s value)	kA	50	40	63	50
First pole-to-clear factor		1.3	1.5	1.3	1,3
Peak short-circuit withstand current Rated closing, latching and short time carrying current	kA (peak)	137	110	173	137
Transformer Limited Fault (TLF)	kA	3 - 10		12	
Rated line-charging capacitive switching		Class C2		Class C2	
Mechanical endurance		Class M2		Class M2	
Breaking time		40 - 46 ms 2 - 2.3 cycles @ 50 Hz 2.4 - 2.7 cycles @ 60 Hz		40 - 46 ms 2 - 2.3 cycles @ 50 Hz 2.4 - 2.7 cycles @ 60 Hz	

*For other values, please contact GE Vernova.

Gas Data*

The functioning of this equipment relies upon SF₆, a fluorinated greenhouse gas.

	SF ₆
Average mass of gas/mixture in the equipment (kg / lbs)*	17.8 / 39.2
GWP ₁₀₀ of gas/mixture (CO ₂ -equivalent)	24,300
CO ₂ -eq of gas/mixture in the equipment (t _{CO₂-eq} / short tons _{CO₂-eq})*	432.5 / 476.8

*For information purposes only. It varies depending on the equipment considered.

For more information, visit
governova.com/grid-solutions

GE Vernova reserves the right to make changes to specifications of products described at any time without notice and without obligation to notify any person of such changes.

© 2026 GE Vernova and/or its affiliates. All rights reserved. GE and the GE Monogram are trademarks of General Electric Company used under trademark license.



GEA-N50010
English
260430